Ruijie | Reyce



RG-EW1300G 1300M Wi-Fi 5 Dual-band Gigabit Mesh Router

DATASHEET




Highlights

- 802.11 ac wave2
- Five omnidirectional & foldable antennas providing strong Wi-Fi signals
- Full coverage, easy setup, and seamless roaming
- 96 concurrent connections
- Easy network management at your fingertips with Reyee Router App




Highlight Features



AC1300 Dual Band WiFi Meets your Smooth Networks Needs

You can effortlessly connect multiple devices and enjoy seamless streaming using the dual 2.4GHz and 5GHz bands.




Concurrently Support Multiple Devices Connection

Dual-Band integration together with the MU-MIMO technology offer low interference and fast speed internet to up to 96 terminals simultaneously.











Highlight Features

 \mathbf{C}

Guest Wi-Fi

Smart Home

2

Blacklist Disabled

Open to all guests

Eco Mode

XPress



Set up your home network in **Reyee Router App** in two minutes. More **Life-time Free** functions are waiting for you to Explore.Experience,Expect.

धी Remote Management

 \mathcal{A} Parental Parental Control Control





Specifications

	Basic
Dimensions (W×D×H)	230 mm × 130 mm × 30 mm (9.06 in. × 5.12 in. × 1.18 in. antennas not included)
Weight	0.29 kg (packages not included)
Wi-Fi Standards	Wi-Fi 5 (802.11ac)
MIMO	2.4 GHz, 2×2, MU-MIMO 5 GHz, 2×2, MU-MIMO
Max. Wi-Fi Speed	2.4 GHz: 400 Mbps 5 GHz: 867 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80MHz
Antennas	5
Antennas Type	External Omnidirectional
Antenna Gain	2.4 GHz: 4.5 dBi 5 GHz: 5.5 dBi
WAN Port	1×10/100/1000 Base-T
LAN Ports	3×10/100/1000 Base-T
Recommended Users	32
Max. Users	96
Power Supply	DC 12V/1.0A
Power Consumption	< 12 W
Operation Frequency Bands	802.11b/g/n: 2.400 GHz to 2.483 GHz 802.11a/n/ac: 5.150 GHz to 5.350 GHz 802.11a/n/ac: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply
Transmit Power	General: CE EIRP: \leq 20dBm (2.4GHz) \leq 27dBm (5GHz) \leq 20dBm 2400~2483.5MHz(Bluetooth) Myanmar: 2400~2483.5MHz \leq 20dBm(EIRP) ; 5150~5350MHz \leq 23dBm(EIRP) ; 5470~5725MHz \leq 30dBm(EIRP) ; 5725~5850MHz \leq 30dBm(EIRP) ;





Basic	
Receive Sensitivity	2.4 GHz:20MHz 802.11b: -91.5 dBm(1 Mbps) 802.11g: -88.5 dBm(6 Mbps), -71 dBm(54 Mbps) 802.11n: -88dBm(MCS0), -69 dBm(MCS7) 5 GHz:20MHz 802.11n: -92 dBm(MCS0), -71 dBm(MCS7) 802.11a: -89 dBm(6 Mbps), -74 dBm(54 Mbps) 802.11ac: -89dBm(MCS0), -65dBm(MCS8)
Operating Temperature	-10 °C to +40 °C (14 °F to 113 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE
Wireless	
OFDMA	-
MU-MIMO	\checkmark
BSS Coloring	-
Maximum Number of SSIDs	6
SSID Hiding	\checkmark
Band Steering	\checkmark
Guest Wi-Fi	\checkmark
WPA/WPA2	\checkmark
WPA3	\checkmark
Roaming	Layer 2 Roaming
Blacklist	\checkmark
Reyee Mesh	\checkmark
Mesh Pairing by Hardware	\checkmark
Mesh Pairing by Mesh Button	\checkmark
Mesh Pairing by Eweb	\checkmark
Recommended Hop Count	≤5





	Wireless
Wi-Fi Optimization	\checkmark
QoS (WMM)	\checkmark
WPS	-
Transmission Power Adjustment	\checkmark

Hardware	
CPU	MT7621DA
Flash	16 MB
RAM/SDRAM	128 M Byte
Color	Black
System LED Indicator	\checkmark
Reyee Mesh LED Indicator	\checkmark
Reyee Mesh Button	\checkmark
Power Button	-
Reset Button	\checkmark
	Outer Diameter: 5.5 mm Inner Diameter: 2.1 mm

DC Connector Dimensions

Outer Diameter: 5.5 mm Inner Diameter: 2.1 mm Length: 9.0 mm (Outer Diameter: 0.22 in. Inner Diameter: 0.08 in. Length: 0.354 in.)

WAN	
Static IP	\checkmark
DHCP	\checkmark
РРРоЕ	\checkmark
Learning PPPoE Account & Password	\checkmark
VLAN Tagging	\checkmark





	LAN
DHCP Server	\checkmark
Client List	\checkmark
Static IP Assignment	\checkmark
Port-Based Flow Control	\checkmark
	Features
TR069	\checkmark
ΙΡν6	\checkmark
DDNS	\checkmark
IPTV	\checkmark
Alarm	\checkmark
Diagnosis	\checkmark
UPnP	\checkmark
ARP Binding	\checkmark
Port Mapping	\checkmark
DMZ Host	\checkmark
Rate Limitation of Terminals	\checkmark
Hardware Acceleration	\checkmark
MAC Address Cloning	\checkmark
Cloud Management	\checkmark
Repeater Mode	\checkmark
WISP Mode	\checkmark
Security	
PPTP VPN Server	\checkmark
PPTP VPN Client	\checkmark





	System
L2TP VPN Client	-
Parental Control	Time Schedule
Protect TCP Flood Attacks	\checkmark
Protect ICMP Attacks	-
Protect UDP Flood Attacks	-
	System
Default Access/Password	192.168.110.1 No Password Required by Default
URL Access	\checkmark
Local Upgrade	\checkmark
Online Upgrade	\checkmark
APP Upgrade	\checkmark
Syslog	\checkmark
Backup	\checkmark
Factory Reset	\checkmark
Language	Chinese English Vietanmese Turkish Indonesian Thai traditioanl Chinese Spanish Russian Arabic Ukrainian Czech Italian



Package Contents

Package Information	RG-EW1300G
Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Warranty Card	1
Cat5E UTP Cable	1

Rujje Rcycc

Redefine your easy network

Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved. No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd. Website: https://reyee.ruijie.com/en-global