

MIFARE 1 S50 ISO CARD

PC.MIFARE.1K



Meets ISO standards for thickness; use with all direct image or thermal transfer printers.

Passive, no-battery design allows for an infinite number of reads Strong, flexible and resistant to cracking and breaking.

MIFARE 1 S50 ISO CARD



PC.MIFARE.1K

Technical Specification

Description	1K Byte, R/W, 13.56MHz, Data retention of 10 years, Write endurance 10,000 cycles		
IC types	MIFARE Standard MF1 IC S50 NXP founded by philips		
Frequency	13.56MHz		
Physical	Thickness	0.8mm	± 0.04mm
	Width	53.98mm	± 0.05mm
	Length	85.60mm	± 0.013mm
	Weight	5.8g	± 0.5g
	Color	White	
	Surface	Matt or Glossy	
Printing	Printable with offset, silkscreen, personalizing.		
	Printable with ink Jet numbering (various different format)		
Material	PVC, PET		
MagStripe	Optional Loco 350 Oe, Hico650 Oe, 2750 Oe and 4000 Oe at ISO position.		
Temperature	-10°C and + 50°C		



Ordering Information

PC.MIFARE.1K

EntryPass Mifare ISO card



www.entrypass.net

Malaysia

No. 40, Jalan TPP 1/10, Taman Industri Puchong, Batu 12 Jalan Puchong, 47160 Puchong Selangor Darul Ehsan, Malaysia.
Tel : +603 8068 1929
Fax : +603 8062 6937
Email : info@entrypass.net

Singapore

No. 1, UBI View, #03-03, Focus ONE Building, Singapore 408555.
Tel : +65- 6841 7242
Fax : +65- 6841 3937
Email : info@entrypass.net

Indonesia

Jl. Raya Lodan No. 2, kompl. Ruko Lodan Centre Blok. P 10, Jakarta Utara 14430, Indonesia.
Tel : +62 21 6983 3153
Fax : +62 21 690 3005
Email : info@entrypass.net

A securityhub group company

